

## SPECIFICATION

Quality		: <b>BOULDER</b>
Product definition		: Colour Placement Loop tufting
Gauge		: 1/10"
No. of tufts	ISO 1763	: ± 141732/m <sup>2</sup>
Pile fibre		: 100% solution dyed nylon
Pile weight	ISO 8543	: 710 gr/m <sup>2</sup> ± 5%
Pile height	ISO 1766	: 2-4 mm ± 5%
Primary backing		: PET woven - ± 150gr/m <sup>2</sup>
Tile backing		: Polyflex
Total thickness	ISO 1765	: 6.50 mm ± 5%
Total weight	ISO 8543	: 4800 gr/m <sup>2</sup> ± 7,5%
Tile size		: 50 x 50 cm (± 19.7" x 19.7")
Tiles per box		: 20

## PERFORMANCE

Use classification	method en 1307	: 33
Castor chair test	EN 985	: A, continuous use
Abrasion	ISO 12951	: pass
Vettermann test	ISO 10361/EN 1471	: pass
Thermal isolation	ISO 8302	: 0.088 m <sup>2</sup> K/W
Dimensional stability	EN 986	: pass
Luxery/Comfort	EN 1307	: classe 1
Sound Absorption	ISO 140-8	: 24 dB



## ELECTROSTATIC PROPERTIES

Walk on test	ISO 6356	: < 2.0 kV
Horizontal electrical resistance	ISO CD 10965	: 3x10 <sup>8</sup> Ω
Vertical electrical resistance	ISO CD 10965	: 4x10 <sup>10</sup> Ω
Static loading		: anti-static

## FLAME PROPERTIES

Reaction to fire	EN ISO 11925-2	
	EN ISO 9239-1	: B <sub>fl</sub> - s1
Hot metal nut test	BS 4790	: Low Radius

## COLOUR FASTNESS PROPERTIES

Light	ISO 105 B02	: > 5
Rubbing, dry	ISO 105 X12	: 4.5
Rubbing, wet	ISO 105 X12	: 5.0
Shampoo	BS 1006	: 4.5
Water	ISO 105 E01	: 4.5
Water stains	TNO W 6024	: 5.0

## GENERAL

Recommended maintenance:  
Pile direction:

Best results are obtained when cleaned with a dry shampoo method.  
Directional arrows are printed on the back of each tile.  
Best results are obtained when laid checkerboard.

Laying instructions:

Tiles require no underlay, nailing, gluing or sewing and may be laid loose on a flat, dry, non-slippery floor. When tiles are laid on parquet, vinyl or in open areas larger than 30 m<sup>2</sup> it is advisable to use double sided adhesive tape on every 8th row or a tackifier.

## COLOURS

003 Antracite	015 Light Grey
006 Blue/Grey	007 Earth

008 Dark Brown	016 Brown
201 Sand	010 Dark grey
Felt Backing	Polyflex Backing



